



Glass and Solid Door
Models Available

HYC-55GE/FE



Wall-mounted
Installation Optional



User-side/Left-right
Reversible Door



Low Noise



Low Power



Frost-free

Pharmacy Refrigerator

Scope of Application

Used for the storage of medicines, vaccines, reagents, biological products, and other items that require a temperature between 2–8°C in home medicine refrigerators, hospice and home care settings, emergency medication storage at nurse stations, community hospitals, etc.

Innovative Design Features

- Built-in Wall-embedded Installation
- Support Left/ Right Reversible Door
- Low-noise Operation



AWTech
Advanced Worldwide Technologies



127566 Россия, Москва,
Алтуфьевское шоссе, дом 48, корпус 1
+7 (499) 346-74-93
info@awt.ru
www.haierus.ru

Группа компаний AWTech – официальный партнер Haier Biomedical.
Официальный дистрибьютор на территории Российской Федерации.
Приглашаем к сотрудничеству коммерческие организации

Product Features



Reversible Double-layer Electric Heating Tempered Glass Door



Ultra-efficient & Quiet: 1.1 kWh/day Low Power, 36dB(A) Library-level Noise



2~8°C Precise Temp Control, Electronic Board with Digital Display, Factory Preset 5°C



Multi-fault Safety Alarm, 24h Power-off Temp Display & Alarm, Optional Remote Interface




Air-cooled Design, Fluorine-free Hermetic Compressor, Wide Voltage 187~242V, CE Certified

Product Details



Product Dimension



Specifications

	Model		HYC-55GE	HYC-55FE
Technical Data	Cabinet Type		Counter-top / Wall-mounted Optional, Glass Door	Counter-top / Wall-mounted Optional, Solid Door
	Climate Class		N, 16~32°C	N, 16~32°C
	Cooling Type		Forced Air Cooling	Forced Air Cooling
	Defrost Mode		Auto	Auto
	Refrigerant		R600a	R600a
	GWP (Global Warming Potential)		20	20
	Sound Level (dB(A))		42	40
Performance	Temperature Range (°C)		2~8	2~8
Control	Will the fan stop automatically when opening the door		Y	Y
	Controller		Microprocessor	Microprocessor
	Display		LED	LED
Electrical Data	Power Supply (V/Hz)		220~240/50	220~240/50
	Power (W)		190	190
Dimensions	Capacity (L/Cu.Ft)		55 / 1.94	55 / 1.94
	Net/Gross Weight (approx)	kg	/	/
		lbs	79.4 / 90.4	79.4 / 90.4
	Interior Dimensions (W*D*H)	mm	400*387*422	400*387*422
		in	15.75*15.24*16.61	15.75*15.24*16.61
	Exterior Dimensions (W*D*H)	mm	495*550*545	495*550*545
		in	19.49*21.65*21.46	19.49*21.65*21.46
	Packing Dimensions (W*D*H)	mm	560*610*625	560*610*625
		in	22.05*24.02*24.61	22.05*24.02*24.61
Alarms	Container Load (20'/40'/40'H)		/	/
	High/Low Temperature		Y	Y
	High Ambient Temperature		Y	Y
	Door Ajar		Y	Y
	Power Failure		Y	Y
	Low Battery		Y	Y
	Sensor Error		Y	Y
	USB Communication Failure		Optional	Optional
	Remote Alarm		Y	Y
	Audible and Visual Alarm		Y	Y
Accessories	Roller		2	2
	Foot		2	2
	Porthole		1 R	1 R
	Shelves/Basket		1/1	1/1
	Printer		N/A	N/A
	Chart Recorder		N/A	N/A
	USB Interface		Optional	Optional
	RS485		N/A	N/A
Others	Certification		CE, DIN13277 (Optional)	CE, DIN13277 (Optional)

*Haier Biomedical reserves the right to change products and specifications without prior notice.